

UTIFORM Quattro

Continuous Mixing Grouting System
連續混合灌漿系統

窄的寬度足夠通過門框QUATTOR適合於噴漿於灌漿
Narrow enough to easily roll through doorways, the Quattro is ideal for both spray and pour applications.

ChemGrout's UF Quattro

系統特點 **System features:**

Built-in air compressor

All electric power

Precision water control

8 full bag hopper capacity

5 to 13 gpm

Pressures up to 450 psi

Pumping distance up to 130'
height up to 66'
(based on materials)



The versatile Quattro sprays mortars as well as pumps self-leveling underlayments.

NEW from ChemGrout®

Portable
可攜帶
Easy to use
容易使用
Versatile
用途多

完整自容的理想單元
**Complete self-contained
unit ideal for:**

- EIFS
- Fireproofing
- Stucco
- Plaster
- Self-leveling underlayments
- Mortar sprayer

UTIFORM Quattro

Self-contained, with built in air compressor and water pump, the Quattro delivers a non-stop, steady material flow for a variety of spray and pour applications. Dry materials are conveyed from the hopper via a metering star wheel into the mixing chamber. Precision water controls ensure that the proper amount of water is added. The benefits of a single operator, superior material consistency and flow rates of up to 13 gpm, translates into big savings in both time and money. Control boxes are hermetically sealed to protect them from dust and water. Automatic shutoff systems, remote control, extra rotor/stator, grout/air hoses, spray wand, hopper cover and tool kit are standard. Optional pneumatic silo conveyor is available.

完整的系統包括:

二機器、100尺噴漿管、空氣管、備用轉子、固定子、噴漿機和工具組

**Complete System includes:
Machine, 100' grout and
air hose, spare rotor/stator,
spray wand and tool kit.**

大漏斗及持有8個箱包
Large hopper hold 8 full
bage

內有空壓機作為噴泥漿沙漿
及防火料
Built in air compressor for
spraying mortar, stucco & fire-
proofing

流量:
5-13加侖
壓力:
450 psi

**Flow rates:
5 to 13 gpm
Pressures:
to 450 psi**

密封控制箱
Sealed control box

大車輪可鎖住
Large wheels with lock

需3相20安培440V
Requires 440V, 3 phase, 20
amps

堅固輕巧機箱
Sturdy, lightweight chassis

精確水控制系統
Accurate water control
system

規格 Specifications

Maximum output	5 to 13 gpm	Air compressor	8.8 CFM, 72psi, 1.2HP
Pumping distance	130 ft.	Water pressure required	42psi
Pumping height	66 ft.	Electrical connection	440 V, 60Hz, 3 phase, 20 amps
Pumping pressure	450 psi	Size	44"L x 26"W x 58"H
Power of mixing motor	7.5 HP	Weight	408 lbs.
Power of feed motor	1.0 HP	Loading height	34"



High outputs and a consistent discharge provide a perfect fit for pumping self-leveling underlayments.



Convenient height for loading, hopper holds 8 full bags!



Durable hopper cover protects against contamination and doubles as dust shield.



Built-in handles for lifting by two people allows for easy movement.



Unit disassembles in minutes for easy transportation.